WBP MELAMINE COMMERCIAL PLYWOOD

WBP Commercial Plywood is a plywood with the same as ordinary commercial plywood, but the glue is used to bond Melamine WBP fillers, which makes the plywood resistant to boiling to until 8 hours but still not detached.

Brand PCV THUAN PHAT **Standard sizes** 1220mmx2440mm, **Standard thickness** 11mm Thickness tolerant: +/- 0.3mm Surface Bintangor **Core veneer** Hardwood: Acacia/Eucalyptus/Combine Glue WBP Melamine **Moisture Content** <12% (less than twelve percent) Wood material Legally Source Plantation Wood Origin Vietnam Density 590 - 615 kg/m3 Packaging

Panels are packed in crates with metal straps then put into container by forklifts.

	Crate per	Panel	Cubic
Thickness	container	per	meter per
		Crate	container
12mm	16	82	40-46
15mm	16	65	
17mm	16	58	
18mm	16	55	

***This is standard container packaging for international shipping for your reference.

PCV THUAN PHAT GROUP VIETNAM Headquarter: PCV THUAN PHAT

Head Office/Factory: Nghia Lo Village, Chi Dao Ward, Van Lam District, Hung Yen Province, Viet Nam.

Mobile: (whatsapp/skype/viber): 84-868914282

Email: phungthanhvan2021@gmail.com